

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** CORNICE CEMENT C500 / BASEBOND B300

**Synonyms** BASEBOND • BLUE CIRCLE SOUTHERN CEMENT BASEBOND • BLUE CIRCLE SOUTHERN CEMENT  
CORNICE CEMENT • CORNICE CEMENT

### 1.2 Uses and uses advised against

**Uses** CEMENT • MASONRY ADHESIVE • PLASTERING

### 1.3 Details of the supplier of the product

**Supplier name** BORAL AUSTRALIA

**Address** Trinita T2, Level 3, 39 Delhi Road, North Ryde, NSW, 2113, AUSTRALIA

**Telephone** (02) 9220 6300

**Website** <http://www.boral.com.au>

### 1.4 Emergency telephone numbers

**Emergency** 13 11 26 (Poisons Information Centre)

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

### 2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

### 2.3 Other hazards

No information provided.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
CALCIUM SULPHATE HEMIHYDRATE	10034-76-1	600-067-1	65 to 98%
LIMESTONE (CALCIUM CARBONATE)	1317-65-3	215-279-6	<31%
KAOLIN	1332-58-7	310-194-1	<10%
MICA	12001-26-2	601-648-2	<10%
TALC	14807-96-6	238-877-9	<3%
CALCIUM HYDROXIDE	1305-62-0	215-137-3	<2%
QUARTZ (CRYSTALLINE SILICA)	14808-60-7	238-878-4	<2%
STARCH	9005-25-8	232-679-6	<2%
ETHYLENE VINYL ACETATE	-	-	<2%
POLYVINYL ALCOHOL (PVA)	9002-89-5	618-340-9	<2%

**Ingredient Notes** Depending on the source materials, this product may contain trace amounts of respirable crystalline silica (quartz and cristobalite), but unlikely to exceed 0.1% (wt.).

## 4. FIRST AID MEASURES

**4.1 Description of first aid measures**

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>First aid facilities</b>	Eye wash facilities should be available.

**4.2 Most important symptoms and effects, both acute and delayed**

Although present only in trace amounts, it is worth noting that chronic exposure to respirable crystalline silica at higher levels could result in lung fibrosis (silicosis), and Chronic Obstructive Pulmonary Disease (COPD). Chronic exposure to cementitious dusts may also result in COPD. Principal symptoms of silicosis and COPD are cough and breathlessness. Respirable Crystalline Silica (RCS) is classified as carcinogenic to humans (IARC Group 1).

**4.3 Immediate medical attention and special treatment needed**

Drinking glycerin, gelatin solutions, or large volumes of water may delay the hardening of this product in the stomach. Surgical relief of obstruction, particularly at the phlorus, may be required.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Use an extinguishing agent suitable for the surrounding fire.

**5.2 Special hazards arising from the substance or mixture**

Non flammable. May evolve toxic gases (sulphur oxides) when heated to decomposition.

**5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

None allocated.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Moisten with water to prevent a dust hazard and place in sealable containers for disposal.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are tightly sealed, adequately labelled and protected from physical damage.

**7.3 Specific end uses**

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Calcium carbonate (Limestone, Marble, Whiting)	SWA [AUS]	--	10	--	--
Calcium hydroxide	SWA [AUS]	--	5	--	--
Calcium hydroxide	SWA [Proposed]	--	1	--	--
Calcium sulphate	SWA [Proposed]	--	1.5	--	--
Calcium sulphate (a)	SWA [AUS]	--	10	--	--
Kaolin (Inspirable dust)	SWA [AUS]	--	10	--	--
Kaolin (Respirable dust)	SWA [AUS]	--	2	--	--
Mica	SWA [AUS]	--	2.5	--	--
Quartz (respirable dust)	SWA [AUS]	--	0.05	--	--
Quartz (respirable dust) (Precautionary advice)	WorkSafe VIC	--	0.02	--	--
Starch (a)	SWA [AUS]	--	10	--	--
Talc (no asbestos fibres)	SWA [AUS]	--	2.5	--	--
Talc, (containing no asbestos fibres)	SWA [Proposed]	--	2	--	--
Vinyl acetate	SWA [AUS]	10	35	20	70

#### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

#### PPE

- Eye / Face** Wear dust-proof goggles.
- Hands** Wear PVC or rubber gloves.
- Body** When using large quantities or where heavy contamination is likely, wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Class P1 (Particulate) respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	OFF-WHITE POWDER
<b>Odour</b>	PLASTER ODOUR
<b>Flammability</b>	NON FLAMMABLE
<b>Flash point</b>	NOT RELEVANT
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	7.5 to 8.5
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	2.3 to 2.4
<b>Solubility (water)</b>	INSOLUBLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT RELEVANT
<b>Lower explosion limit</b>	NOT RELEVANT
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	> 300°C

**9.1 Information on basic physical and chemical properties**

Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

**10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization will not occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with aluminium (when heated), diazomethane, phosphorus (at high temperatures) and oxidising agents.

**10.6 Hazardous decomposition products**

May evolve toxic gases (sulphur oxides) when heated to decomposition.

**11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

**Acute toxicity** This product is expected to be of low toxicity. Based on available data, the classification criteria are not met.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
LIMESTONE (CALCIUM CARBONATE)	> 5000 mg/kg (rat)	--	--
KAOLIN	> 5000 mg/kg (rat)	> 5000 mg/kg (rat)	--
TALC	> 5000 mg/kg (rat)	--	--
CALCIUM HYDROXIDE	7300 mg/kg (mouse)	--	--
POLYVINYL ALCOHOL (PVA)	14700 mg/kg (mouse)	--	--

<b>Skin</b>	Not classified as a skin irritant. Contact may result in mild irritation, redness and rash.
<b>Eye</b>	Not classified as an eye irritant. However, direct contact may result in mild irritation, lacrimation, pain and redness.
<b>Sensitisation</b>	Not classified as causing skin or respiratory sensitisation.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Not classified as a carcinogen. Crystalline silica is classified as carcinogenic to humans (IARC Group 1). Chronic exposure to crystalline silica may result in lung fibrosis (silicosis). However, due to the low levels present, chronic health effects are not anticipated with normal use.
<b>Reproductive</b>	Not classified as a reproductive toxin.
<b>STOT - single exposure</b>	Not classified as causing organ damage from single exposure. However, over exposure may result in irritation of the nose and throat, with coughing.
<b>STOT - repeated exposure</b>	Not classified as causing organ damage from repeated exposure.
<b>Aspiration</b>	Not classified as causing aspiration.

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

The main component/s of this product are not anticipated to cause any adverse effects to the environment.

**12.2 Persistence and degradability**

Product is persistent and would have low degradability

**12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate

**12.4 Mobility in soil**

A low mobility would be expected in a land fill situation

**12.5 Other adverse effects**

The main component/s of this product are not anticipated to cause any adverse effects to plants or animals.

---

**13. DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

**Waste disposal** Reuse where possible. No special precautions are normally required when handling this product. Reuse or recycle where possible. Alternatively, dispose of to appropriately licensed landfill facility. Contact the manufacturer/supplier for additional information (if required).

Note: Considered same as plaster of paris, casting plaster

**Legislation** Dispose of in accordance with relevant local legislation.

---

**14. TRANSPORT INFORMATION**

---

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	None allocated.	None allocated.	None allocated.
<b>14.2 Proper Shipping Name</b>	None allocated.	None allocated.	None allocated.
<b>14.3 Transport hazard class</b>	None allocated.	None allocated.	None allocated.
<b>14.4 Packing Group</b>	None allocated.	None allocated.	None allocated.

**14.5 Environmental hazards**

Not a Marine Pollutant.

**14.6 Special precautions for user**

Hazchem code None allocated.

---

**15. REGULATORY INFORMATION**

---

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
All components are listed on AIIC, or are exempt.

---

**16. OTHER INFORMATION**

---

**Additional information** PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:  
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**



## Revision Information

### Revision History

Revision	Date	Description
4.0	28/07/2020	Scheduled Update
3.0	Jan 2020	Standard SDS Review
2.0	Jan 2015	Converted to GHS
1.0	Jan 2015	Initial SDS creation

### Review Team

SME Reviewers	Subject Matter
Manager- Technical Services (NSW/ACT), Boral Construction Materials	Quality
WHS Advisor, QLD Office	Safety
Environmental Sustainability Manager, Cement	Environment & Community
National Compliance Officer, Heavy Vehicles, Logistics	Transport & Dangerous Goods
National Health & Hygiene Manager	Health & Hygiene
<b>National Manager - Cement, Boral Quarries</b>	<b>Product Custodian</b>